

Genovese General Purpose/Anchor Chain — G30

FINISH: Hot Dip Galvanized

PACKAGING: Full & Half Drums, Pails, Crates

Exceeds DIN 764 G30 specifications

D764
G30
Embossed/ft

Genovese General Purpose/Anchor Chain is low carbon steel general purpose/anchor chain with an ISO short pitch link. It is used in applications where high tensile strength is not required. Please check manufacturer's specification prior to use. Certificate available upon request.

PID	WIRE DIA mm	INSIDE LENGTH mm	OUTSIDE WIDTH mm	WORKING LOAD kg	BREAKING LOAD kg	WEIGHT kg/m	PACKAGE	LENGTH m
10325311	5	23	19.5	300	1200	0.500	Drum	500
10325134	6	29	23	360	1440	0.710	Pail	50
10325136	6	29	23	360	1440	0.710	Half Drum	200
10325312	6	29	23	360	1440	0.710	Crate	1000
10325313	7	30.5	26.5	500	2000	1.010	Drum	300
10325135	8	35	30.5	650	2600	1.315	Half Drum	50
10325137	8	35	30.5	650	2600	1.315	Drum	200
10325314	8	35	30.5	650	2600	1.315	Crate	800
10325138	10	40	38	1100	4400	2.070	Drum	100
10325315	10	40	38	1100	4400	2.070	Crate	500
10325139	12	47.5	44.5	1500	6000	3.090	Crate	100
10325316	12	47.5	44.5	1500	6000	3.090	Crate	300
10325140	14	52.5	53	2000	8000	4.120	Crate	100
10325317	14	52.5	53	2000	8000	4.120	Crate	200
10325318	16	55	57	2800	11200	5.330	Crate	200
10325319	18	63	63	3500	14000	6.800	Crate	100
10325320	20	70	69	4500	18000	8.360	Crate	100
10325321	22	78	79	5000	20000	10.610	Crate	100
10325141	24	86	81	5300	21200	11.900	Pail	-
10325142	26	91	87	6300	25200	14.000	Pail	-
10325143	28	98	94	7500	30000	16.500	Pail	-
10325323	28	98	94	7500	30000	16.500	Crate	50
10325144	30	105	102	8500	34000	19.000	Pail	-
10325324	30	105	102	8500	34000	19.000	Crate	50

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications. Please see Page 26 for Packaging Details.