

Grade L Windlass Chain - G30



Grade L is a low carbon steel chain specifically manufactured to Australian Standard AS2321-2006. Used for anchoring and mooring applications, Grade L calibrated short-link design ensures proper fit for most Australian windlasses. Hot dip galvanized for the best protection against corrosion and abrasion. Check manufacturer's specification prior to purchase.

Finish: Hot Dip Galvanized

Packaging: Full & Half Drums, and Pails

Trade Size mm	Wire Diameter		Inside Dimensions				Working Load Limit	
	mm	in.	Length		Width		kg-force	pound-force
			mm	in.	mm	in.		
6	6	.24	18	.71	7.5	.3	454	1000
8	8	.31	24	.94	10	.39	816	1800
10	10	.39	30	1.2	12.5	.49	1270	2800
13	13	.51	39	1.5	16.3	.64	2041	4500

Trade size mm	Plastic Pail					Half Drum					Full Drum				
	Weight		Length		Part ID	Weight		Length		Part ID	Weight		Length		Part ID
	Kg	Lbs	m	ft.		Kg	Lbs	m	ft.		Kg	Lbs	m	ft.	
6	48	106	60	196.9	CHGL6X60	126	276	157	515	CHGL6X157	252	554	315	1033.5	CHGL6X315
8	48	106	34	111.6	CHGL8X34	125	275	88	288.7	CHGL8X88	249	547	175	574.1	CHGL8X175
10	50	110	22	72.2	CHGL10X22	125	276	55	180.4	CHGL10X55	251	552	110	361	CHGL10X110
13	50	110	13	42.7	CHGL13X13	124	272	32	105	CHGL13X32	247	543	64	210	CHGL13X64

Please see page 3 for packaging details.

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications