

DIN766 Windlass Chain - G30



DIN766 chain uses a low carbon steel chain specifically designed for anchoring applications. Hot dip galvanized short link chain, calibrated to latest DIN766 standard. Each link is calibrated to ensure proper fit for most metric windlasses. Check manufacturer's specification prior to purchase.

Finish: Hot Dip Galvanized

Packaging: Full Drums

Trade Size mm	Wire Diameter		Inside Dimensions				Working Load Limit	
	mm	in.	Length		Width		kg-force	pound-force
			mm	in.	mm	in.		
6	6	.24	18.5	.73	7.2	.28	408	900
7	7	.28	22	.87	8.4	.33	635	1400
8	8	.31	24	.94	9.6	.38	816	1800
10 P28	10	.39	28	1.1	12	.47	1275	2810
10 P30	10	.39	30	1.2	12	.47	1275	2810
11	11	.43	31	1.22	13.2	.52	1610	3550
13	13	.51	36	1.4	15.6	.61	2041	4500
14	14	.55	41	1.6	16.8	.66	2551	5625
16	16	.63	45	1.77	19.2	.76	3186	7025

Trade Size mm	Part ID	Full Drum			
		Kg	Lbs	Length / m	Length / ft.
6	CHD7666X315	252	554	315	1033.46
7	CHD7667X225	250	549	225	738.2
8	CHD7668X175	249	547	175	574.15
10 P28	CHD76610P28X110	257	566	110	360.89
10 P30	CHD76610P30X110	260	573	110	360.89
11	CHD76611X88	249	548	88	288.71
13	CHD76613X62	247	544	62	203.41
14	CHD76614X57	250	549	57	187
16	CHD76616X44	252	554	44	144.36

Please see page 3 for packaging details.

Warning: Working Load Limit must not be exceeded. Not to be used for lifting or hoisting applications